



FIBER OPTIC TEMPERATURE SENSOR

TS4

Key Features

- Temperature range: -200 °C to +200 °C
- Electrically non-conductive
- Immunity to RFI, EMI, NMR and micro-wave radiation
- High accuracy
- Stable and repeatable measurements
- GaAs-based temperature sensor

Applications

- Harsh chemical conditions, e.g. nuclear
- Offshore temperature measurements
- Natural gas pipelines and storage tanks
- Battery testing



WEIDMANN

FIBER OPTIC
TEMPERATURE SENSOR

TS4

TECHNICAL SPECIFICATION

Name of sensor	TS4
Measurement range	-200 °C to +200 °C
Inertia	Up to 7 K/s
Accuracy *1	+/- 0.2 K
Fiber Ø	200 µm
Sensor standard lengths	2m up to 20m
Connector type	ST with metallic ferrule (-40 to 85 °C)
Signal conditioner	Compatible with all Weidmann fiber optic thermometers

DESCRIPTION

The fiber optic temperature probe TS4 is especially designed for the use in chemical aggressive and nuclear environments. Its increased resistance comes with no loss in accuracy and temperature range.

Its mechanical setup results in a immunity to RFI, EMI, NMR and microwave radiation. The temperature sensor guarantees a measuring range from -200 °C to +200 °C with an accuracy*1 of +/-0.2 K.


The fiber optic temperature probe is completely non-conductive. Thanks to its special PTFE protection the TS4 probe resists even aggressive chemical concentrations inside the measurement environment – with a maximum diameter of 2 mm.

All fiber optic temperature sensors can be connected to the fiber optic temperature measurement devices (FOTEMP), delivers accurate and complete reliable, stable and repeatable values.

Starting at a light wave length of 850 nm GaAs (gallium arsenide) becomes optical translucent. Since the position of the band gap is temperature dependent, it shifts about 0.4 nm/K. The sensor cable can be produced in different lengths without influencing the accuracy of the measurement result.

We are always anxious to adjust our offer to your special needs. In case of any further questions about individual measurement problems, lengths of sensors or connector types, please contact us.

DIMENSION



*1 Statement only possible with analysis unit. See data sheet of the measurement device for information about technical data.

DISCLAIMER – PLEASE READ CAREFULLY

This datasheet is based on Weidmann's knowledge as of the date of its publication. Instructions and explanations, while substantially accurate, are non-binding. Illustrations, specifications and average values are subject to change, do not guaranty actual product characteristics or specifications and are intended only to indicate possible uses of the Weidmann products. Customers alone must determine whether the products are suitable for their particular use and intended application and assume all risk and liability for unsafe or improper use or application. Weidmann shall not be liable for catalogue printing or other errors, for changes to Weidmann products or for any defects in the technical data or use of any information contained in the catalogue. Weidmann reserves the right always to revise the catalogue at any time, without notification. No part of this catalogue can form any part of or amend or alter any provision of any contract with respect to the Weidmann products. With respect to products in this catalogue, Weidmann disclaims all warranties, express or implied, including but not limited to, implied warranties of merchantability and fitness for a particular purpose. Weidmann shall not be liable for direct, indirect, special, incidental or consequential damages arising out of the purchase or use of products in this datasheet.